

REAL ESTATE REGULATORY AUTHORITY, PUNJAB

First Floor, Block-B, Plot No. 3, Madhya Marg, Sector-18, Chandigarh, 160 018

Quotation for Audio/Video Conference System

Sno	Description	Qty	Unit	Unit Rate	Amount
AUDIO SYSTEM					
1	Wall mount speaker for high-fidelity music and speech reproduction. Water and dust protected IP 65. Sound pressure level at 30W/1W: 90/105dB. Effective Frequency Range 100 Hz to 18.5 kHz Rated power-30W. Make: Bosch Model LB2-UC30-D1	4	Nos		
2	Mixer Amplifier 120 Watts . 4 mic level balanced inputs . Built-in speech filter for increased intelligibility. Priority & VOX operation. Telephone and emergency input connections. Three stereo line input selection. Selectable 2 to nechime . Separate Bass & Treble control Make Bosch Model PLE-1ME120-2IN	1	No.		
3	Handheld Wireless Mic system that has a min of 14-hour battery life from two AA alkaline batteries. Cardioid polar pattern, Dynamic microphone ,frequency response 83Hz-18kHz, RF sensitivity < 1.0 Uv, Image rejection >55dB, Dyanmic range >95dB and receiver having 30 channels possible, .S/N ratio >100dB A, dynamic range >95db B, distortion <1 %, frequency band: 618-634MHz, modulation: +/-40kHz Makes: Electro-Voice. Model: R 300-HD-A	2	Nos		
4	Lapel Wireless Mic system that has a min of 14-hour battery life from two AA alkaline batteries. Cardioid polar pattern. Dynamic microphone, frequency response 83Hz-18kHz, RF sensitivity < 1.0 Uv, Image rejection >55dB, Dyanmic range >95dB and receiver having 30 channels possible, S/N ratio >100dB A, dynamic range >95db B, distortion <1 %, frequency band: 618-634MHz, modulation: +/-40kHz Make: Electro-Voice Model R300- L	1	No.		
5	Wireless Gooseneck Microphone with Switchable omni, cardioid, supercardioid or hypercardioid polar patterns, Impedance: Low-Z balanced 200Ω, extended low frequency response and switchable high-pass filter. Make: Electro-Voice Model: PC-Satellite	1	No.		
VIDEO SYSTEM					
6	2x2 55inch video wall 4K resolution Audio In (L/R) Pin Jack x 1 set (Side) (Shared with VIDEO In), Speaker Out External Speaker Terminal, 20 W [10 W/8 Ω + 10 W/8 Ω], DVI-I Out DVI-I 29-pin x 1, IR Transmitter In/Out IR x 1/ x 1, Screen size 55-inch (1387 mm), Brightness 700 cd/m ² , Contrast Ratio 1200:1, Response Time 12 ms (G to G), Effective Display Area (W x H) 1209 x 60 mm, Number of Pixels (H x V) 1920 x 1080 pixels, Panel Type LCD IPS Panel/D-LED , Dynamic Contrast 500000:1 Make Panasonic Model LH55VW3KD	1	Set		
7	4 Inputs to 1 Output HDMI Switcher, supports HDR10, HDCP2.2, Ultra HD/4K Make Key-Digital Model KD-S4x1	1	No.		

REAL ESTATE REGULATORY AUTHORITY, PUNJAB

First Floor, Block-B, Plot No. 3, Madhya Marg, Sector-18, Chandigarh, 160 018

8	Wireless Presentation and Collaboration Solution. With any laptop or mobile device, users can view, edit and comment on documents in real time, share files and chat with individuals or multiple participants simultaneously. The solution can show up to four screens on the main display. From any laptop or mobile device, students, teachers or any in-room meeting participant can view the main display, edit documents together in real time, share any size file, turn the main display into a digital whiteboard, and more Make Kramer Model VIA Connect Pro	1	No.		
9	Round Table Mount HDMI, Cat-6 and power Multi-Connection Solution with Pneumatic Lid. Make: Kramer	3	Nos		
CABLE CONNECTOR AND ACCESSORIES					
10	Equipment rack 17 U Make: Comrack	1	No.		
11	HDMI via CAT5e/6 Extender Transmitter and receiver set: Key digital KD-X222	3	No.		
12	1.5 meter HDMI cable Make : Key Digital	8	No.		
13	2 core 1.5 sq mm speaker cable. Make: Polycab	100	Mtrs		
14	UTP Cat-6 cable. Make: D-Link	100	Mtrs		
15	32 MM PVC conduit	100	Mtrs		
16	Installation charges				
17	GST				
	Total				

General Terms & Conditions of Payment

Warranty:

AMC:

Payment Term:

Delivery Period:

Details of the Earnest Money:

Demand Draft No _____

Dated _____

Amount _____

DATED

Signature of Authorised Representative
with Rubber Stamp